

# HEAVY SEPERATION

CENTRIFUGES FOR ENERGY & ENVIRONMENT



 **ALLIED**  
Centrifuge Technologies

**G SERIES** 

 **ALLIED**  
Industrial Dynamics  
[www.alliedindyn.com](http://www.alliedindyn.com)

- Bitumen Processing
- General De-watering
- Solids Control
- Waste Stream Recycling
- Tunneling
- Micro Tunneling
- Mining & Minerals
- Matt Cleaning
- Site Remediation
- Kaolin Clay & Calcium Carbonate Processing
- Waste Oil Stream Recycling
- Manure Processing
- Waste Fluid Treatment
- Bio Fuel
- Sump & Tank Cleaning
- Lagoon De-sludging
- Hydro-vac Waste Facilities
- Tailings Recovery
- Chemical Manufacturing
- Drilling Fluids Management
- Phosphorus Recovery
- Crude Processing
- Bentonite & Titanium Dioxide Manufacturing
- Bio-ethanol Manufacturing
- Dio-diesel Manufacturing

| Unit        | Hydraulic Feed Capacity | Phase | Empty Decanter Weight   | Beach Angle | Total Installed Power | Bowl Diameter    |
|-------------|-------------------------|-------|-------------------------|-------------|-----------------------|------------------|
| <b>GX3</b>  | 1-10 M3/h<br>(3-44 gpm) | 2     | 900 kg<br>(1984l bs)    | 6°          | 15hp                  | 254 mm<br>(10")  |
| <b>GX4</b>  | 60 M3/h<br>(264 gpm)    | 2     | 3600 kg<br>(7437 lbs)   | 6°          | 75hp                  | 356 mm<br>(14")  |
| <b>GX6</b>  | 120 M3/h<br>(528 gpm)   | 2     | 4536 kg<br>(10000 lbs)  | 7°          | 120hp                 | 457 mm<br>(18")  |
| <b>G7</b>   | 156 M3/h<br>(686 gpm)   | 2     | 7552 kg<br>(16650 lbs)  | 6°          | 180hp                 | 559 mm<br>(22")  |
| <b>GX8</b>  | 180 M3/h<br>(793 gpm)   | 2     | 8460 kg<br>(18650 lbs)  | 7°          | 200hp                 | 660 mm<br>(26")  |
| <b>GX9</b>  | 240 M3/h<br>(1056 gpm)  | 2     | 10886 kg<br>(24000 lbs) | 7°          | 260hp                 | 762 mm<br>(30")  |
| <b>GX10</b> | 545 M3/h<br>(2400 gpm)  | 2     | 18143 kg<br>(40000 lbs) | 7°          | 400hp                 | 1016 mm<br>(40") |